


D Sub-Miniature Connectors


The standard series provides a high quality range of D subminiature connectors in 9, 15, 25, 37 and 50 way versions, and with the option of solder bucket, straight and PCB solder, wire wrap, edge mount, SMT, or press fit termination styles all of which are offered with a wide range of plating options. Connector shells are finished with tin plate over nickel or yellow chromate over zinc. Polarisation is achieved by the keystone shape of the mating plug and socket.




Contact Arrangements




Size 1 = 9 contacts




Size 2 = 15 contacts



Size 3 = 25 contacts



Size 4 = 37 contacts



Size 5 = 50 contacts

Note: view as seen from back of socket


Materials and Finishes

- Insulator: thermoplastic rated UL94 V-O
- Shell: steel, yellow chromate or tin plate finish
- Contacts: copper alloy, screw machined or stamped, with gold, tin or selective plating


Operating Characteristics

- Current rating:
Machine contacts: 5 Amps typically
Stamped contacts: 3 Amps typically
- Temperature range: -55°C to 155°C typically
- Operating voltage: 250 V
- Resistance: per mated contact pair max. 35m ohm (MIL-C-24308)
- Insulation resistance: 5000M ohm per mated contact pair
- Volume resistance: 10⁶ ohm cm (ASTM-D257)
- Dielectric strength: 50 kV/mm


Termination Styles - straight contacts




Style S
Solder Bucket




Style P
Printed Circuit
0.6 (.024) dia.



Style W
Wire Wrap
0.6 (.024) square



PCB Edge Mount



Style H
Press Fit
0.8mm (0.031") square