

## Patch Leads for use with G.703 Modular Balun System

A wide range of standard and custom built leads and cable assemblies are available for use with Cambridge Connectors' Modular Balun System and other telecommunication applications. Manufactured to EN ISO9002 standards they are 100% tested to ensure the highest quality.



### Coaxial Patch Leads

#### 75 Ohm Coaxial Patch Leads - Standard European Styles

|              |                |
|--------------|----------------|
| BNC Plug     | - BNC Plug     |
| BNC Plug     | - 1.6/5.6 Plug |
| BNC Plug     | - 1.0/2.3 Plug |
| 1.6/5.6 Plug | - 1.6/5.6 Plug |
| 1.6/5.6 Plug | - 1.0/2.3 Plug |
| 1.0/2.3 Plug | - 1.0/2.3 Plug |

Options -

- Cable lengths of 0.5; 1; 3; 5; 10 Metres
- Standard PVC or LSOH Cable

#### 75 Ohm coaxial Patch leads - Standard UK Styles

|                |                    |
|----------------|--------------------|
| BNC Plug       | - Type 43 Female   |
| BNC Plug       | - Type 43 DDF Male |
| BNC Plug       | - HDC 43 DDF Male  |
| Type 43 Female | - Type 43 Female   |
| Type 43 Female | - Type 43 DDF Male |
| Type 43 Female | - HDC 43 DDF Male  |
| 1.6/5.6 Plug   | - Type 43 Female   |
| 1.6/5.6 Plug   | - Type 43 DDF Male |
| 1.6/5.6 Plug   | - HDC 43 DDF Male  |
| 1.0/2.3 Plug   | - Type 43 Female   |
| 1.0/2.3 Plug   | - Type 43 DDF Male |
| 1.0/2.3 Plug   | - HDC 43 DDF Male  |



Options -

- Cable lengths of 0.5; 1; 3; 5; 10 Metres
- Standard PVC or LSOH Cable

All of these 75 ohm patch leads are also available as 4, 8 or 16 way Multiway Coaxial Cable Assemblies with equal or staggered length ends.

## Patch Leads for use with G.703 Modular Balun System

### Cat 5e Patch Leads

#### RJ45 Patch leads - to T568B (258A) Standard

|           |   |
|-----------|---|
| RJ45 Plug | - RJ45 Plug (shielded plugs with FTP cable)   |
| RJ45 Plug | - RJ45 Plug (unshielded plugs with UTP cable) |

#### Options -

- Cable lengths of 0.5; 1; 3; 5; 10 Metres
- Coloured boots
- Coloured cable  
Standard colours are Grey; Beige; Black; Blue; Red; Green; Yellow




### Telco Patch Leads

#### Telco Connector Patch Cables - to 258A Standard

|                     |                       |
|---------------------|-----------------------|
| 50 way Telco Male   | - 50 way Telco Male   |
| 50 way Telco Male   | - 50 way Telco Female |
| 50 way Telco Female | - 50 way Telco Female |
| 50 way Telco Male   | - Open End            |
| 50 way Telco Female | - Open End            |

#### Options -

- Cable lengths of 3; 5; 10 Metres
- Screened or Unscreened Cat 3 cable with 90° or 180° hood
- Unscreened Cat 5 cable with 90° or 120° hood
- Standard PVC or LSOH cable



### Hydra Cable Assemblies to 258A Standard

|                     |   |
|---------------------|---|
| 50 way Telco Male   | - 6 x RJ45 Plug (with 4 pair Cat 5 UTP cable) |
| 50 way Telco Female | - 6 x RJ45 Plug (with 4 pair Cat 5 UTP cable) |

#### Options -

- Cable lengths of 3; 5; 10 Metres
- Standard PVC or LSOH cable
- 12 x RJ45 Plug (with 2 pair UTP cable - non 258A standard)
- 90°; 120°; 180° hoods
- 50 way Telco to D Subminiature connector
- 50 way Telco to DIN 41612 connector

